

In this work, hydrophobic carbon cloth (HCC) was chemically activated by the facile oxidation method using a mixture of concentrated acid ($\text{H}_2\text{SO}_4\text{:HNO}_3$) followed by ammonium hydroxide (NH_4OH) treatment to make it a suitable electrode/current collector for energy storage device. It was found that the treated carbon cloth (TCC) turned hydrophilic by ...

1 Introduction. Since their discovery in 2011, 2D transition metal carbides or carbonitrides (MXenes) [1, 2] became a focal point of nanomaterials, notably for electrochemical energy storage. [3-6] The general formula of MXene is $\text{M}_{n+1}\text{X}_n\text{T}_x$ ($n = 1-3$), where M represents an early transition metal, X is carbon and/or nitrogen, and T_x stands for the surface ...

The insulation properties and energy storage density of the biaxially oriented films were significantly improved by a simple film formation post-treatment. The impregnation treatment effectively suppressed the leakage current of the film at a high electric field. ... Finally, the BOPVDF films with functionalized surface treatment can be ...

A series of novel composite phase change materials (PCMs) were tailored by blending PEG and five kinds of diatomite via a vacuum impregnation method. To enlarge its pore size and specific surface ...

Compared to traditional surface treatment methods, $\text{Na}_2\text{S}_2\text{O}_8$ solution treatment can induce more profound structural evolution without necessitating high-temperature calcination, thus reducing the demands on process conditions and equipment and offering greater process controllability. ... (EVs), and renewable energy storage systems, the ...

The demand for energy has increased tremendously around the whole world due to rapid urbanization and booming industrialization. Energy is the major key to achieving an improved social life, but energy production and utilization processes are the main contributors to environmental pollution and greenhouse gas emissions. Mitigation of the energy crisis and ...

However, studies on the surface modification of ZIF-8 using the EAB-assisted approach for energy storage are limited. Here, ZIF-8 was synthesized and post-modified with Ag NPs utilizing EABs for energy storage applications. The varying amount of Ag nanoparticles on ZIF-8 was deposited to evaluate the electrochemical performance.

Improved dielectric properties and energy-storage densities of BaTiO_3 -doped PVDF composites by heat treatment and surface modification of BaTiO_3 BaTiO_3 ,poly(vinylidene fluoride),modification,dielectric properties,energy storage ...

Therefore, we can conclude that heat treatment and surface modification of doped BT particles could become new approaches to enhance the energy storage performance of the BT/PVDF composites, which ...

The progress of novel, low-cost, and environmentally friendly energy conversion and storage systems has been instrumental in driving the green and low-carbon transformation of the energy sector [1]. Among the key components of advanced electronic and power systems, polymer dielectrics stand out due to their inherent high-power density, fast charge-discharge ...

It is the first megawatt-grade hydrogen energy storage power station in China, which realizes the functions of electrolytic hydrogen production, hydrogen storage, hydrogen sale and hydrogen energy generation. ... Surface modification treatment. It is well known that ball milling is one of the common preparation processes of hydrogen storage ...

This review summarizes the recent developments in the synthesis of hydrogel/aerogel-based 3D-printed materials and their applications in wastewater treatment and energy storage. The high porosity, surface area, and adjustable properties of 3D-printed hydrogel/aerogel materials make them and their employment in practical applications interesting.

The large-scale energy storage with low cost can be realized with combining the advantages of RFBs and PEMFCs and omit the disadvantages of them. ... But after the air plasma treatment, the surface of the carbon paper became completely hydrophilic and the contact angle could not be recorded because that the surface of carbon paper became wet ...

Biochar is a carbon-rich solid prepared by the thermal treatment of biomass in an oxygen-limiting environment. It can be customized to enhance its structural and electrochemical properties by imparting porosity, increasing its surface area, enhancing graphitization, or modifying the surface functionalities by doping heteroatoms.

We alkylated silica aerogels to make them hydrophobic for effective impregnation and storage of a phase change material (PCM). As a result of this surface modification treatment, the aerogel scaffold exhibited an average increase of 20.9-34.7% in the PCM uptake with an improved thermal energy storage capacity and stability.

Graphene is a two-dimensional carbon allotrope with a thickness of just one atom. It is composed of a honeycomb arrangement of hexagonal crystalline structure with sp^2 carbon atoms in a conjugated system. Although graphene was theoretically conceived in the 1940s, it lacked the thermodynamic stability required for reliable operation in everyday environments [20,21,22].

New energy storage apparatus that can effectively store electrical energy are considerably needed for different applications ranging from wearable electronics ... Furthermore, it was revealed that after the N_2/O_2 -plasma treatment, the surface of the nanofibers becomes rougher by an invasion of the high energy plasma particles. Download ...

Under the excitation impact by external energy, the fast electrons act on different gas molecules; thus, the reactive species, such as excited atomic O, N, S, and P radicals, as well as molecular O_2^+ , N_2^+ , H_2^+ , NH_2^- , and OH $^-$ radicals, can be generated under certain atmosphere composition and operating conditions. The interactions between the ...

Indeed, the impact of the flame treatment was evaluated by considering the two different durations which were 5 and 60 s. Flame treatment (Fig. 5) was conducted approximately 5 cm from the top of the main reaction zone to the prepared metallic nozzles' free surfaces. Flame treatment was performed at a constant rate of 14 mm/s.

Therefore, energy storage devices are needed to maintain the energy supply. Among these devices, metal-ion batteries, redox batteries, and the hydrogen cycle based on fuel cells ... This can be done by surface treatment, including profiling, or surface deposition of other materials. In particular, studies describing successive deposition of ...

We alkylated silica aerogels to make them hydrophobic for effective impregnation and storage of a phase change material (PCM). As a result of this surface modification treatment, the aerogel ...

The unique properties of 2D MXenes, such as metal-like electrical conductivity and versatile surface chemistry, make them appealing for various applications, including energy storage. ...

Capacitors exhibit exceptional power density, a vast operational temperature range, remarkable reliability, lightweight construction, and high efficiency, making them extensively utilized in the realm of energy storage. There exist two primary categories of energy storage capacitors: dielectric capacitors and supercapacitors. Dielectric capacitors encompass ...

Obtaining high-value nitrogen-containing carbon nanosheets with ultrahigh surface area from waste sludge for energy storage and wastewater treatment. Author links open overlay panel Zhengliang Du a b 1, Qiandi Wang a c 1, Youjing Du d, Qiongying ... The specific surface areas (SSAs) and porosity distributions were calculated according to BET ...

a, 1H NMR spectra of DMPESI in anhydrous DMSO- d_6 after six months of storage in ambient air. The H_2O peak in DMSO- d_6 is at 3.3 ppm (vertical dashed blue line): the signal is absent in the ...

After heat treatment at a suitable temperature, PESU can form a more compact locally ordered structure. ... The energy storage densities (U_e) of it at the maximum electric field are $4.1 J/cm^3$, ... The surface modifier of BZCT@ZnO NFs contains hydroxyl to promote the compatibility of the inorganic BZCT@ZnO NFs and the organic polymer matrix ...

Surface functionalization or modification to introduce more oxygen-containing functional groups to biochar is an effective strategy for tuning the physico-chemical properties and promoting follow-up applications. In this study, non-thermal plasma was applied for biochar surface carving before being used in contaminant removal

and energy storage applications. ...

Inorganic perovskite $\text{CsPbI}_{3-x}\text{Br}_x$ was prepared via a one-step spin-coating method, and surface treatment by fluorine-containing salts such as KF, RbF and CsF were first investigated. Similar ...

Because of their outstanding properties, activated carbons (such as a high surface area, a high degree of microporosity, atoxicity, and conductivity) are widely used as, e.g., an adsorbent in water or gas purification as well as for energy storage and conversion [1-4]. The chemical and electrochemical properties of activated carbons strongly ...

Graphene oxide (GO), the most popular derivative of graphene, has attracted tremendous attention due to its reputable properties such as excellent electrical, catalytic and thermal properties, high conductivity and chemical stability, as well as large surface area [1, 2]. As a result, GO is utilized in a wide variety of applications including electronics, optics, energy storage, ...

Web: <https://eriyabv.nl>

Chat online: <https://tawk.to/chat/667676879d7f358570d23f9d/1i0vbu11i?web=https://eriyabv.nl>