

Design of a KNN-BZT Ceramic with High Energy Storage Properties and Transmittance under Low Electric Fields Zhonghua Dai, Fanbo Zhang, Muhammad Nasir Rafiq, Chenxi Liu, Xin Wang, Shuitao Gu,* ... The sintering process of KNN ceramic is relatively harsh, resulting in low energy storage characteristics of Received: November 30, 2022 Accepted ...

For dielectric capacitors, energy storage characteristics includes recoverable energy density (W_{rec}), total energy storage density (W), and energy storage efficiency (η), is calculated by such formulas [26], [34], [35]:
(2) $W = \int_0^{P_{max}} E dP$ (3) $W_{rec} = \int_0^{P_r} E dP$ (4) $\eta = \frac{W_{rec}}{W} \times 100\%$ here P_{max} , P_r and E are the maximum ...

Meanwhile, the $x = 0.175$ samples also achieved a high recoverable energy storage density of 3.71 J/cm^3 under the breakdown electric field of 360 kV/cm . The designed KNN-based dielectric materials were expected to be applicable to the energy storage capacitor with standed high operating temperature.

This study presents the synthesis of KNN ceramic structural, dielectric, impedance, and energy storage behavior using the solid-state reaction method. Preliminary structural studies were conducted using X-ray diffraction and Raman spectroscopy at room temperature. The results indicate that KNN exhibits orthorhombic symmetry based on the XRD ...

Here, $\text{Bi}(\text{Li}_{0.5}\text{Nb}_{0.5})\text{O}_3$ (BLN) was chosen to modify the $(\text{K}_{0.5}\text{Na}_{0.5})\text{NbO}_3$ (KNN)-based ceramics to optimize the optical transmittance and energy storage characteristics simultaneously. On the one hand, the grain ...

The optimum energy storage properties can be attained at $x = 0.35$, accompanied by energy efficiency of 84.87% , a promising energy storage density of 2.3 J/cm^3 and good temperature stability of ...

Fig. 3, Fig. 4 show the morphologies and grain size distribution of the BSZT-KNN-based nanoceramics with different nano-additives respectively. The densities of the "BT + ST" series, "BST" series, "BT" series and "ST" series are 5.323 g/cm^3 , 5.309 g/cm^3 , 5.590 g/cm^3 and 5.141 g/cm^3 , respectively. The relative densities of the samples exceed 0.96 , and the ...

a The dielectric behaviour of KNN-Bi,Sb,Zr (multi-element doped KNN) ceramic over a temperature range of $130\text{-}700 \text{ K}$. b The dielectric and c piezoelectric properties of the multi-elements and ...

Request PDF | Adjusting the Energy-Storage Characteristics of $0.95\text{NaNbO}_3 - 0.05\text{Bi}(\text{Mg}_{0.5}\text{Sn}_{0.5})\text{O}_3$ Ceramics by Doping Linear Perovskite Materials | Passive electronic components are an ...

It indicates that the BZZ completely diffused into the KNN lattice and form a solid solution with KNN

ceramic. The previous studies have confirmed that pure KNN ceramics at room temperature have an orthorhombic phase structure, with a characteristic peak near 45° for (202) and (020). ... To further study the energy storage characteristics of 0 ...

The transparency is up to 69.27% in the near-infrared region (1344 nm) and the energy storage density is 2.16 J/cm³ under 170 kV/cm. Moreover, the 0.90KNN-0.10BZT ceramic exhibits a power density (PD) of 17.50 MW/cm³ and the stored energy can be discharged in 1.60 ms at 140 kV/cm.

In the early 21st century, Saito et al. reported a (K_{0.5}Na_{0.5})NbO₃-based (KNN-based) ceramic with a piezoelectric coefficient up to 416 pC/N [9]. Since then, researchers have focused on a thorough analysis of the structure and properties of KNN-based ceramics [10], [11], [12]. Furthermore, increasing attention has been paid to the energy storage and optical ...

Next-generation advanced high/pulsed power capacitors rely heavily on dielectric ceramics with high energy storage performance. However, thus far, the huge challenge of realizing ultrahigh ...

Superior energy storage performance was achieved in the 0.7BST-0.3KNN ceramics with a breakdown strength (E_b) of 510 kV/cm, a recoverable energy storage density (W_{rec}) of 4.10 J/cm³, and an energy storage efficiency (η) of 80 %, which was fairly stable over the temperature range of 30-100 °C. Since multiple cations with different valence ...

It should be noted that energy losses inevitably occur in the energy conversion process involved in piezoelectric energy harvesting [2]. To better evaluate the energy harvesting ability of piezoelectric materials, in the 33-mode PEHs, Priya combines the off-resonance and on-resonance conditions, giving a dimensionless figure of merit (DFOM) [11]: (1) $DFOM = d_{33} / g_{33}$...

Lead-free piezoelectric ceramics gained an increased attention due to their high piezoelectric properties combined with the absence of lead and other potentially hazardous elements. In this work, we used a unimorph cantilever beam arrangement to study piezoelectric energy harvesting in pristine K_{0.5}Na_{0.5}NbO₃ (KNN) and Fe₂O₃ modified KNN (KNFN) ...

This study demonstrates a strategy for constructing the phase boundary with MPB feature, settling the problem of temperature instability in (K, Na)NbO₃-based ceramics. Piezoceramics can achieve the conversion of mechanical energy and electrical energy, endowing electromechanical devices with the function of energy conversion.

The comparisons of energy storage characteristics of BNBSTC + K_{0.8}N_{0.2} ceramics and other BNT-based ceramics are exhibited in Table 2. In order to further evaluate the work stability in various environments, the energy storage properties of BNBSTC + K_{0.8}N_{0.2} ceramics at different frequency, ...

The W_{rec} and i values of dielectric energy storage ceramics can be calculated via the polarization-electric field (P-E) loop according to the equations below: $W_{tal} = \int_0^{P_{max}} E dP$, $W_{rec} = \int_{P_r}^{P_{max}} E dP$, $i = \frac{W_{rec}}{W_{tal}} \times 100\%$ where P_{max} , P_r , and E represent maximum polarization, remnant polarization, and applied electric field, respectively. Based on the ...

Semantic Scholar extracted view of "Amelioration on energy storage performance of KNN-based transparent ceramics by optimizing the polarization and breakdown strength" by C. Li et al. ... Simultaneous Improvement of Energy Storage Characteristics and Temperature Stability in K_{0.5}Na_{0.5}NbO₃-Based Ceramics via LiF Modification. Qifan Chen ...

In this study, a design strategy is proposed to optimize the energy storage characteristics and transparency of ceramics by introducing nanodomains, increasing the band gap energy and reducing the grain size.

Dielectric capacitors have become indispensable energy storage devices in many fields due to their fast charging and discharging, high power density, and long lifespan.¹ The practical applications of current dielectric ceramic capacitors in sophisticated electronic components and cutting-edge pulsed power systems have been significantly hindered by their ...

Based on the polarization-electric (P-E) curves, the vital parameters of evaluating energy storage properties can be computed by the following equations [10]: (1) $W = \int_0^{P_{max}} E dP$, (2) $W_{rec} = \int_{P_r}^{P_{max}} E dP$, (3) $i = \frac{W_{rec}}{W} \times 100\%$. where W and W_{rec} stand for the total energy storage density during the charging procedure ...

In summary, ultra-high temperature stability and piezoelectric coefficient were achieved in the 3T ceramics. Both the T/O phase local distortion associated with the O-T ...

Moreover, the ceramic also has some features for energy storage. Er-doped 0.91(K_{0.5}Na_{0.5})NbO₃-0.09Sr(Mg_{0.5}Ta_{0.5})O₃ transparent fluorescent ceramics were prepared according to the traditional solid-phase method. ... to improve luminescence characteristics to a greater extent, it is necessary to get closer to the rule of rare-earth doping. Up ...

DOI: 10.1016/j.jallcom.2023.173199 Corpus ID: 266339467; Novel lead-free KNN-based ceramic with giant energy storage density, ultra-high efficiency and excellent thermal stability via relaxor strategy

The addition of KNN can obviously improve energy storage performance (ESP). At 255 kV cm⁻¹, $x = 0.2$ produced excellent ESP with recoverable energy storage density (W_{rec}), amazingly normalized response (x), efficiency (i) and maximum polarization (P_{max}) are 3.38 J cm⁻³, 132.55 J kV⁻¹ m⁻², 85.4 %, and 45.76 mC cm⁻² ...

Here, Bi(Li_{0.5}Nb_{0.5})O₃ (BLN) was chosen to modify the (K_{0.5}Na_{0.5})NbO₃ (KNN)-based ceramics to

optimize the optical transmittance and energy storage characteristics simultaneously. On the one hand, the grain ...

The newly developed ceramic, (1-x) KNN-xBSZ, exhibited remarkable performance characteristics, including an energy storage density of 4.13 J/cm³, a recoverable energy storage density of 2.95 J/cm³ at a low electric field of 245 kV/cm, and an energy storage efficiency of 84 %. Additionally, at 700 nm, the 0.875KNN-0.125BSZ sample displayed a ...

A high effective energy-storage density (W_{rec}) ~ 1.234 J/cm³; with efficiency (η) ~ 74.7% are acquired at 90 kV/cm. The energy-storage performance is revealed an excellent fatigue resistant ...

Web: <https://eriyabv.nl>

Chat online: <https://tawk.to/chat/667676879d7f358570d23f9d/1i0vbu11i?web=https://eriyabv.nl>